## **Product Data Sheet**

Specification Number 1480 Revision 02 VYCERIN™ GL97 ASTM D7640 Antifreeze Grade. 99.5 % Vegetable Glycerin



**Code:** VYCERIN™ GL97 **Description:** ASTM D7640 Antifreeze

Grade. 99.5 % Vegetable

Glycerin

**Customer:** CHI - House

Packaging: Bulk/Drum/Tote

## **Test Specifications**

|   | Parameter   | Units        | Minimum | Maximum | Comments                        |
|---|---|--------------|---------|---------|---------------------------------|
| * | Glycerine   | %            | 99.5    |         | Sodium Meta Periodate<br>Method |
| * | Specific Gravity @<br>25°C  |              | 1.261   |         |                                 |
| * | Color (APHA)  |              |         | 10      |                                 |
| * | Fatty Acids &<br>Esters   | ml 0.5N NaOH |         | 1.0     |                                 |
| * | Appearance  |              | Pass    |         | Clear, colorless liquid         |
| * | Odor  |              | Pass    |         | Slight, characteristic          |
| * | Moisture by Karl<br>Fischer   | %            |         | 0.5     |                                 |
| * | рН  |              | 6       | 8       | 50 % solution                   |
| * | Chloride ion  | ppm          |         | 10      |                                 |
| С | Total Nitrite,<br>Nitrate,<br>Phosphate                               | ppm          |         | 10      | Certified                       |
| С | Silicon   | ppm          |         | 10      | Certified                       |
| * | Sulfate ion   | ppm          |         | 10      |                                 |
| С | Iron  | ppm          |         | 2       | Certified                       |
| С | Boron   | ppm          |         | 10      | Certified                       |
| С | Total Aluminum,<br>Calcium, Copper,<br>Iron, Magnesium,<br>Lead, Zinc | ppm          |         | 5       | Certified                       |

Notes: \* Indicates parameters to be reported on COA

**C** Certify

## **COA Comments: Standard COA**

This product meets the current ASTM Glycerine Specification for Engine Coolant Grade Glycerin. We certify the following: Methanol  $\leq$  10 ppm; Ash  $\leq$  0.01%; Iron  $\leq$  2 ppm; Silicon  $\leq$ 10 ppm; Boron  $\leq$  10 ppm; Total Nitrite, Nitrate and Phosphate  $\leq$  10 ppm; Total Aluminum, Calcium, Copper, Iron, Magnesium, Lead, Zinc  $\leq$  5 ppm.

The information in this publication is believed to be accurate and is given in good faith but no representation or warranty as to its completeness or accuracy is made. Suggestions for uses or applications are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation or warranty, express or implied, is made with respect to information or products including without limitation warranties of merchantability or fitness for a particular purpose or non-infringement of any third party patent or other intellectual property rights including without limit copyright, trademark and designs. Any trademarks identified herein are trademarks of Vantage Oleochemicals, Inc.

**Rev.** 02: 11/28/2016 **ISSUED:** 04/10/2019